



HOW TO USE

- ➡ Using a hard rubber press the grout firmly into the joints ensuring that the joints are completely filled.
- ➡ Clean off the surplus grout from the joint and surface within 15-20 minutes.
- ➡ Do not allow water to flow and run into ungrouted joints.

COVERAGE

- ➡ Depends on the size of the tiles, stone & width of joint.

WARNING

- ➡ Wear Protective Gloves & Goggles.
- ➡ Use a Suitable Dust Mask.



C2-212
TILE
ADHESIVE
GRAY



S1-252
TILE STONE
ADHESIVE
GRAY

H - 40 FLEX
HEAVY STONE
ADHESIVE



S2-335
STONE
ADHESIVE
GRAY & WHITE



WHITE SBR WATER PROOFING
SYSTEM



SUPER EPOXY GROUT



FLEXISET PU ADHESIVE

EPOXY TILES GROUT COVERAGE CHART

Approx sq.ft. coverage per 1 kg.

Tile Size x Thickness	Joint Width						
	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
100 x 100 x 3	53	35	27	18	14	11	09
150 x 150 x 4	60	40	30	50	15	12	10
200 x 150 x 5	54	36	27	18	14	11	09
150 x 300 x 6	53	35	26	18	13	10	08
300 x 300 x 6	79	53	40	26	20	16	13
450 x 300 x 7	81	54	41	27	21	16	14
600 x 600 x 8	118	79	59	39	30	24	20
600 x 900 x 10	102	68	51	24	25	20	11
900 x 900 x 12	118	79	59	39	30	24	20

APPLICATION

- ➡ Ceramic Floor
- ➡ Wall Tiles
- ➡ Quarry Tiles
- ➡ Stone
- ➡ Marble
- ➡ Mosaics

BENEFITS

- ➡ Weather Proof
- ➡ Easy Maintenance
- ➡ Non Shrinking
- ➡ High Strength
- ➡ Anti Fungal and Anti Bacterial
- ➡ 100% Stain Free and Waterproof
- ➡ Hygienic and Hard Wearing
- ➡ Crack Resistant

Mfg. & Mkt. by:

DuwFix Chemicals Pvt. Ltd

Survey No. 247, Block no. 233, Shed no. 18, Dev Campus,
Canal Road, Near Euro School, Ring Road, Kosmada,
Surat-395006Cell: 9499502775 / 9499502776
E-mail: info@duwfix.com Web.: www.duwfix.com

HOW TO USE / इस्तेमाल करने का तरीका



Mix hardener & Resin properly.
हार्डनर और रेजिन को अच्छी तरह मिलाएं।



Add Filler Properly During Mixing,
Until Homogeneous Plaster is Obtained.
एक समान पेस्ट बनने तक, मिश्रण में धीरे-धीरे
फिलर को मिलाएं।



Fill the Joint with the Help of Squeeze
trowel.
खबर की थापी से जॉइंट को भरें।



Clean the Tiles with the help of Sponge
after 15-20 minutes.
15-20 मिनट के बाद टाइल्स को स्पंज की
मदद से साफ करें।



REGULAR SERIES

101 White	114 Baff
102 Quarry Red	115 Platinum
103 Silver	116 Light Green
104 Dusty Rose	117 Alpine Blue
105 Coffee Brown	118 Burgundy
106 Olive Grenn	119 Parchment
107 Tarra Cotta	120 Dark Grey
108 Sandtone	121 Imca Gold
109 Black	122 Mocha
110 Sky Blue	123 Cadmium Red
111 Raven	124 Smoke Grey
112 Ivory	125 Sable
113 Canyon Red	126 Natural Grey



SILVER SERIES

101 White	114 Baff
102 Quarry Red	115 Platinum
103 Silver	116 Light Green
104 Dusty Rose	117 Alpine Blue
105 Coffee Brown	118 Burgundy
106 Olive Grenn	119 Parchment
107 Tarra Cotta	120 Dark Grey
108 Sandtone	121 Imca Gold
109 Black	122 Mocha
110 Sky Blue	123 Cadmium Red
111 Raven	124 Smoke Grey
112 Ivory	125 Sable
113 Canyon Red	126 Natural Grey



GOLDEN SERIES

101 White	114 Baff
102 Quarry Red	115 Platinum
103 Silver	116 Light Green
104 Dusty Rose	117 Alpine Blue
105 Coffee Brown	118 Burgundy
106 Olive Grenn	119 Parchment
107 Tarra Cotta	120 Dark Grey
108 Sandtone	121 Imca Gold
109 Black	122 Mocha
110 Sky Blue	123 Cadmium Red
111 Raven	124 Smoke Grey
112 Ivory	125 Sable
113 Canyon Red	126 Natural Grey



RAINBOW SERIES

101 White	114 Baff
102 Quarry Red	115 Platinum
103 Silver	116 Light Green
104 Dusty Rose	117 Alpine Blue
105 Coffee Brown	118 Burgundy
106 Olive Grenn	119 Parchment
107 Tarra Cotta	120 Dark Grey
108 Sandtone	121 Imca Gold
109 Black	122 Mocha
110 Sky Blue	123 Cadmium Red
111 Raven	124 Smoke Grey
112 Ivory	125 Sable
113 Canyon Red	126 Natural Grey



SUPER EPOXY GROUT

THREE PART

